

About Fallshaw

Fallshaw Casters

ISO9001 - 2000 QUALITY MANAGEMENT SYSTEM

Maintaining an effective quality assurance system requires regular internal audits of all our design and manufacturing processes to ensure we are following our quality plans. Surveillance and conformance audits by external auditors give further independent assurance this is happening.

Fallshaw believes that to stay ahead in today's competitive market, you have to be competitively priced, produce quality products and deliver them in a timely manner.

Fallshaw also tests their products ... and nothing tests a product better than a loaded rig of falling steel! Prototypes are given more punishment than we hope our customers could ever dish out. International design standards are used. If we feel the standards are not tough enough - we'll add our own, more stringent, tests.



FALLSHAW CASTERS


Sample Fallshaw Applications



Fallshaw Model Numbering System

MJQ125G/MPPNTBBRY

This example is a 5" ARC 220 swivel plate total brake rig with thermoplastic elastomer wheel and precision ball bearing with berry thread guard



arc casters

Fallshaw ColorWays Thread Guard Color options available on Arc and Zen casters.

- WHT** White
- SIL** Silver
- GPH** Graphite
- INK** Ink
- BRY** Berry
- CPR** Copper
- RST** Russet
- ZBR** Bronze
- TIM** Titanium

zen casters

K

Series Casters




This is the ideal caster for light duty applications. Specifically for indoor functions where a high quality ride, attractive appearance and effective breaking system is required.

TYPICAL APPLICATIONS

- Hospitality
- Food services
- Pharmaceuticals
- Dollies
- Light furniture
- Store displays

MOUNTING OPTIONS



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance

RIG OPTIONS

Swivel Plate
KZP

Swivel Plate
Total Brake
KZPTB

Rigid Plate
KZF

Swivel Hollow
Kingpin
KZH

Swivel Hollow
Kingpin Total
Brake **KZHTB**






BEARING OPTIONS



K SERIES • CAPACITY TO 120



	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rate for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Bearing Type	Wheel Number
Grey Rubber (Natural) 	2.5	7/8	100	3 3/4	2 1/2	P	KSP65/
	3	7/8	100	4 1/8	2 3/4	P	KSP75*/
	4	7/8	110	5 3/16	3 1/4	P	KSP100*/
	4	7/8	110	5 3/16	3 1/4	Q	KSQ100G/
*Thread Guards optional: add "G" before the slash to the wheel code (Example: KSP75G/KZP).							
Polyurethane on Polypropylene 	3	7/8	120	4 1/8	2 3/4	A	KUA75/
	3	7/8	120	4 1/8	2 3/4	Q	KUQ75/
	4	7/8	120	5 3/16	3 1/4	A	KUA100/
	4	7/8	120	5 3/16	3 1/4	Q	KUQ100/
Thermoplastic Elastomer (TPE) 	2.5	7/8	110	3 3/4	2 1/2	A	KJA65G/
	2.5	7/8	110	3 3/4	2 1/2	Q	KJQ65G/
	3	7/8	110	4 1/8	2 3/4	A	KJA75G/
	3	7/8	110	4 1/8	2 3/4	Q	KJQ75G/
	4	7/8	110	5 3/16	3 1/4	A	KJA100G/
	4	7/8	110	5 3/16	3 1/4	Q	KJQ100G/

Rig Numbers	Swivel Plate	Total Brake	Rigid Plate	Hollow Kingpin	Total Brake
					
KZP	KZPTB	KZF	KZH	KZHTB	
					
KZP	KZPTB	KZF	KZH	KZHTB	
					
KZP	KZPTB	KZF	KZH	KZHTB	



Caster Number: KUQ75/KZPTB
This 3" swivel hollow Kingpin total brake rig with grey rubber wheel features a precision ball bearing.

Swivel lead dimension refers to KZP/KZH rigs.
Brake rig swivel lead is 3 1/2".

M

Series Casters



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance


This is the ideal caster for hard working applications. The M caster is the everyday reliable caster that you can depend upon. The quality components ensure functionality which is enhanced by its eye-catching form.

TYPICAL APPLICATIONS


- Hospital beds
- Hospitality
- Food services
- Pharmaceuticals
- Dollies
- Light furniture
- Store displays
- Stock carts
- Institutional

MOUNTING OPTIONS


North American Plate



Standard ISO Plate



Hollow Kingpin



To order delete **N** after rig code:
Example: MSA100G/MZPNTB
changes to MSA100G/MZPTB

RIG OPTIONS

Swivel Plate
MZPN

Rigid Plate
MZFN

Swivel Plate
Total Brake
(Red) **MZPNTB**

Swivel Plate
Direction Brake
(Green) **MZPNDL**

Swivel Hollow
Kingpin **MZH**

Swivel Hollow
Kingpin Total Brake
(Red) **MZHPTB**

Swivel Hollow
Kingpin
Direction Brake
(Green) **MZHDL**

If swivel lead is too large for your application, a shorter pedal is available - ask the factory

BEARING DESCRIPTIONS



	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on normal operation)	Overall Height (Inches)	Swivel Lead (Inches)	Bearing Type	Wheel Number
--	-------------------------	----------------------	---	-------------------------	----------------------	--------------	--------------

Grey Rubber



MS

4	1 5/16	285	5 5/16	3 9/16	A	MSA100G/MSQ100G/MSA125G/MSQ125G/
4	1 5/16	300	5 5/16	3 9/16	Q	
5	1 5/16	300	6 3/8	4	A	
5	1 5/16	330	6 3/8	4	Q	

PVC



MV

3	1 1/4	155	4 3/16	2 7/8	Q	MVQ75G/MVQ100G/MVQ125G/
4	1 1/4	165	5 5/16	3 9/16	Q	
5	1 1/4	175	6 3/8	4	Q	

Rig Numbers	Swivel Plate Total Brake	Swivel Plate Direction Brake	Rigid Plate	Hollow Kingpin	Hollow Kingpin Total Brake	Hollow Kingpin Direction Brake
-------------	--------------------------	------------------------------	-------------	----------------	----------------------------	--------------------------------

MZPN | MZPNTB | MZPNDL | MZFN | MZH | MZHTB | MZHDL

MZPN | MZPNTB | MZPNDL | MZFN | MZH | MZHTB | MZHDL

Swivel lead dimension refers to MZPN/MZH rigs. Brake rig swivel lead is 4 5/8" for 3" diam. wheels and 5" for 4" & 5" diam. wheels.



Caster Number: MSQ100G/MZPNTB
This 4" swivel plate total brake rig with grey rubber wheel features precision ball bearings.

Continued next page

M

Series Casters



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance

M SERIES • CAPACITY TO 330

Continued from previous page

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rated for normal operation)	Overall Height (Inches)	Swivel Lead (Inches)	Bearing Type	Wheel Number
-----------------------------------	--------------------------------	---	-----------------------------------	--------------------------------	---------------------	---------------------

Rig Numbers	Swivel Plate Total Brake	Swivel Plate Direction Brake	Rigid Plate	Hollow Kingpin	Hollow Kingpin Total Brake	Hollow Kingpin Direction Brake

Material	Wheel Diameter	Tread Width	Capacity	Overall Height	Swivel Lead	Bearing Type	Wheel Number
Anti-Static MA	4	1 1/4	175	5 5/16	3 9/16	Q	MAQ100G/
	5	1 1/4	200	6 3/8	4	Q	MAQ125G/
Polyurethane on Polypropylene MU	3	1 1/4	285	4 3/16	2 7/8	Q	MUQ75G/
	4	1 1/4	300	5 5/16	3 9/16	Q	MUQ100G/
	5	1 1/4	330	6 3/8	4	Q	MUQ125G/
Thermoplastic Elastomer (TPE) MJ	3	1 1/4	165	4 3/16	2 7/8	A	MJA75G/
	3	1 1/4	190	4 3/16	2 7/8	Q	MJQ75G/
	4	1 1/4	175	5 5/16	3 9/16	A	MJA100G/
	4	1 1/4	200	5 5/16	3 9/16	Q	MJQ100G/
	5	1 1/4	200	6 3/8	4	A	MJA125G/
5	1 1/4	220	6 3/8	4	Q	MJQ125G/	
Natural Rubber ST	3	1 1/4	190	4 3/16	2 7/8	Q	STQ75G/
	4	1 1/4	200	5 5/16	3 9/16	Q	STQ100G/
	5	1 1/4	220	6 3/8	4	Q	STQ125G/
Rubber Hi Resilience MB	4	1 1/4	300	5 5/16	3 9/16	Q	MBQ100G/
	5	1 1/4	330	6 3/8	4	Q	MBQ125G/

MZPN	MZPNTB	MZPNDL	MZFN	MZH	MZHTB	MZHDL
MZPN	MZPNTB	MZPNDL	MZFN	MZH	MZHTB	MZHDL
MZPN	MZPNTB	MZPNDL	MZFN	MZH	MZHTB	MZHDL
MZPN	MZPNTB	MZPNDL	MZFN	MZH	MZHTB	MZHDL
MZPN	MZPNTB	MZPNDL	MZFN	MZH	MZHTB	MZHDL



Caster Number: MUQ100G/MZH
This 4" hollow Kingpin rig with polyurethane on polypropylene wheel features precision ball bearings

Swivel lead dimension refers to MZPN/MZH rigs. Brake rig swivel lead is 4 5/8" for 3" diam. wheels and 5" for 4" & 5" diam. wheels.

Series Casters



This caster is perfect when a robust caster is required. Although it can bear a greater load it has been designed with style in mind and therefore its polished appearance is an added benefit.

TYPICAL APPLICATIONS


- Hospitality
- Food services
- Dollies
- Store displays
- Stock carts
- Hotel luggage carts
- Heavy duty trolleys




FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance

MOUNTING OPTIONS



RIG OPTIONS



BEARING DESCRIPTIONS



	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on normal operation)	Overall Height (Inches)	Swivel Lead (Inches)	Bearing Type	Wheel Number
Blue Rubber	4	1 1/4	330	5 1/16	3 1/2	A	JBA100/
	4	1 1/4	330	5 1/16	3 1/2	R	JBR100/
	5	1 3/8	395	6 1/8	4 3/8	A	JBA125/
	5	1 3/8	395	6 1/8	4 3/8	R	JBR125/

Thread Guards optional: add "G" before the slash to the wheel code (Example: JBA100G/JZP).

Rig Numbers	Swivel Plate Total Brake	Rigid Plate	Hollow Kingpin	Hollow Kingpin Total Brake
JZP	JZPTB	JZF	JZH	JZHTB



Caster Number: JDR100G/JZH
This 4" swivel hollow Kingpin caster includes Polyurethane with Rubber Seam wheel featuring roller bearings.

Thread guard option requires additional lead time, Consult Factory.
Swivel lead dimension refers to JZP/JZH rigs.
Brake rig swivel lead is 4 13/16".

J Series Casters






FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance



Continued from previous page

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on normal operation)	Overall Height (Inches)	Swivel Lead (Inches)	Bearing Type	Wheel Number	Rig Numbers	Swivel Plate Total Brake	Rigid Plate	Hollow Kingpin	Hollow Kingpin Total Brake
Polyurethane With Rubber Seam												
 JD	4	13/8	485	5 1/16	3 1/2	R	JDR100G/	JZP	JZPTB	JZF	JZH	JZHTB
	5	17/16	550	6 1/8	4 3/8	R	JDR125G/					
Polyurethane on Polypropylene												
 JU	4	1 1/4	615	5 1/16	3 1/2	A	JUA100/	JZP	JZPTB	JZF	JZH	JZHTB
	4	1 1/4	615	5 1/16	3 1/2	R	JUR100/					
	5	1 1/2	660	6 1/8	4 3/8	A	JUA125/					
	5	1 1/2	660	6 1/8	4 3/8	R	JUR125/					
Thread Guards optional: add "G" before the slash to the wheel code (Example: JUA100G/JZP).												
Nylon												
 JN	4	1 1/4	615	5 1/16	3 1/2	N	JNN100/	JZP	JZPTB	JZF	JZH	JZHTB
	4	1 1/4	615	5 1/16	3 1/2	R	JNR100/					
	5	1 3/8	660	6 1/8	4 3/8	N	JNN125/					
	5	1 3/8	660	6 1/8	4 3/8	R	JNR125/					
Thread Guards optional: add "G" before the slash to the wheel code (Example: JNN100G/JZP).												



Caster Number: JDR100G/JZH
This 4" swivel hollow Kingpin caster includes Polyurethane with Rubber Seam wheel featuring roller bearings.

Thread guard option requires additional lead time, Consult Factory.
Swivel lead dimension refers to JZP/JZH rigs.
Brake rig swivel lead is 4 13/16".

O

Series Casters



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance

RIG OPTIONS

Swivel Plate
OZPN



Rigid Plate
OZFN



Swivel Plate
Total Brake
OZPNTB



BEARING DESCRIPTIONS




A robust stamped metal caster. Ideal when moving a heavy load is imperative.

TYPICAL APPLICATIONS


- Hospitality
- Food services
- Stock carts
- Factories
- Industrial

MOUNTING OPTIONS


North American Swivel Plate




Standard ISO Swivel Plate



North American Rigid Plate



Standard ISO Rigid Plate



To order ISO plates delete **N** after rig code:
Example: OUR100/OZPN.
changes to OUR100/OZP.

Wheel Diameter (Inches)		Tread Width (Inches)		Capacity (Lbs) (Based on manual operation)		Overall Height (Inches)		Swivel Lead (Inches)		Bearing Type		Rig Numbers		
Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Wheel Number	Swivel Plate	Total Brake	Rigid Plate
Polyurethane on Polypropylene														
4	2	660	57/16	3 3/4	R	OUR100/	OZPN	OZPNTB	OZFN					
5	2	725	65/16	4 1/4	R	OUR125/								
6	2	790	77/16	4 3/4	R	OUR150/								
8	2	880	9 1/2	6	R	OUR200/								



Caster Number: OUR100/OZPNTB
This 4" swivel plate total brake rig has a Polyurethane on Polypropylene wheel with roller bearings.

Swivel lead dimension refers to OZPN rigs.
Brake rig swivel lead is 5 5/8".

O





Series Casters



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- CoreCoat™ lacquer for superior corrosion protection
- Excellent design and performance

Continued from previous page

	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Plate for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Bearing Type	Wheel Number	Rig Numbers
								Swivel Plate Total Brake Rigid Plate
Grey Rubber								
 OS	4	2	660	57/16	33/4	Q	OSQ100/	OZPN OZPNTB OZFN
	5	2	725	65/16	41/4	Q	OSQ125/	
	6	2	790	77/16	43/4	Q	OSQ150/	
	8	2	880	91/2	6	Q	OSQ200/	
Rubber High Resilience								
 OB	4	2	660	57/16	33/4	Q	OBQ100/	OZPN OZPNTB OZFN
	5	2	725	65/16	41/4	Q	OBQ125/	
	6	2	790	77/16	43/4	Q	OBQ150/	
	8	2	880	91/2	6	Q	OBQ200/	
Rubber on Cast Iron								
 OO	4	111/16	265	57/16	33/4	R	OOR100/	OZPN OZPNTB OZFN
	5	111/16	395	65/16	41/4	R	OOR125/	
	6	111/16	460	77/16	43/4	R	OOR150/	
	8	111/16	550	91/2	6	R	OOR200/	
Nylon								
 ON	4	19/16	770	57/16	33/4	A	ONA100/	OZPN OZPNTB OZFN
	4	19/16	770	57/16	33/4	R	ONR100/	
	5	19/16	835	65/16	41/4	A	ONA125/	
	5	19/16	835	65/16	41/4	R	ONR125/	
	6	19/16	880	77/16	43/4	A	ONA150/	
	6	19/16	880	77/16	43/4	R	ONR150/	
	8	19/16	880	91/2	6	A	ONA200/	
	8	19/16	880	91/2	6	R	ONR200/	

Swivel lead dimension refers to OZPN rigs.
Brake rig swivel lead is 55/8".



Caster Number: OBQ100/OZPN
This 4" swivel plate rig with rubber high resilience wheel features precision ball bearings.

ARC Deluxe Light Duty




The five standard ColorWay options available in the ARC K Series range make it easy to find a caster that suits your design. The ARC K Series capacity range is ideal for light to medium application.

TYPICAL APPLICATIONS

- Hospitality
- Shop displays
- Office equipment
- Furniture

MOUNTING OPTIONS

Swivel Plate Hollow Kingpin




FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- ColorWays to match furniture, display or equipment
- Powder coated rig
- Chicago screw axle, domed both sides
- Excellent design and performance

RIG / BRAKE OPTIONS

Swivel Plate
KPP



Swivel Plate
Total Brake
KPPTB



Swivel Hollow
Kingpin
KPH



Swivel Hollow
Kingpin
Total Brake
KPHTB




BEARING DESCRIPTIONS



Plain Bearing (P)



Precision Ball (Q)



Transparent PVC Tread Polypropylene Core (Plain Bearing)

	3	7/8	110	4 1/8	2 3/4	KVP75/
	4	7/8	110	5 3/16	3 1/4	

KV

Thermal Plastic Elastomer TPE (Precision Ball Bearing)

	2 1/2	7/8	110	3 3/4	2 1/2	KJQ65G/ KJQ75G/ KJQ100G/
	3	7/8	110	4 1/8	2 3/4	
	4	7/8	110	5 3/16	3 1/4	

KJ


Rig Numbers				Color Way Code	ColorWay Description
Swivel Plate	Swivel Plate Total Brake	Hollow Kingpin	Hollow Kingpin Total Brake		
				GRY	Transparent Grey

Rig Numbers	Color Way Code	ColorWay Description			
KPP	KPPTB	KPH	KPHTB	WHT	White Thread Guard
				SIL	Silver Thread Guard
				GPH	Graphite Thread Guard
				INK	Ink Thread Guard
				BRY	Berry Thread Guard

Swivel lead dimension refers to KPP/KPH rigs. Brake rig swivel lead is 3 1/2".



Caster Number: KVP75/KPHTBGRY
This 3" swivel plate total brake rig features a transparent grey wheel and plain bearing.



ARC

Deluxe Medium Duty



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- ColorWays to match furniture, display or equipment
- Powder coated rig
- Chicago screw axle, domed both sides
- Excellent design and performance


The ARC M Series is the hard working caster with a flair of style. It is also available in five standard colors and a powder coated finish, but is more suited to everyday applications.

TYPICAL APPLICATIONS



- Hospital beds
- Hospitality
- Food services
- Pharmaceuticals
- Dollies
- Light furniture
- Store displays
- Stock carts
- Institutional

MOUNTING OPTIONS

North American Plate



Standard ISO Plate



RIG / BRAKE OPTIONS

Swivel Plate
MPPN



Swivel Plate
Total Brake
MPPNTB



Swivel Hollow
Kingpin
MPH




Swivel Hollow
Kingpin
Total Brake
MPHTB



BEARING DESCRIPTION



To order delete **N** after rig code:
Example: MJQ100G/MPPNGPH
changes to MJQ100G/MPPGPH



Thermoplastic Elastomer TPE (Precision Ball Bearing)

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on minimal operation)	Overall Height (Inches)	Swivel Lead (Inches)	Wheel Number
3	1 1/4	190	4 3/16	2 7/8	MJQ75G/ MJQ100G/ MJQ125G/
4	1 1/4	200	5 5/16	3 9/16	
5	1 1/4	220	6 3/8	4	

MJ Note: MJQ wheels were formerly QXQ wheels

Rig Numbers	Swivel Plate Total Brake	Hollow Kingpin	Hollow Kingpin Total Brake	Color Way Code	ColorWay Description
MPPN	MPPNTB	MPH	MPHTB	WHT SIL GPH INK BRY	White Thread Guard Silver Thread Guard Graphite Thread Guard Ink Thread Guard Berry Thread Guard

Swivel lead dimension refers to MPPN/MPH rigs.
Brake rig swivel lead is 4 5/8".



Caster Number: MJQ125G/MPHNTBBRY
This 5" hollow Kingpin total brake rig with thermoplastic elastomer wheel and berry color thread guard features a precision ball bearing.



ZEN

Deluxe Light Duty




The Zen K Series is available in four earth tones that set the tone for any modern living space. It is ideal for light to medium applications. When style is important Zen K Series is for you.

TYPICAL APPLICATIONS

- Hospitality
- Store displays
- Furniture

MOUNTING OPTIONS



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- ColorWays to match furniture, display or equipment
- Powder coated rig
- Chicago screw axle, domed both sides
- Excellent design and performance

RIG OPTIONS

Swivel Plate
Total Brake
KPP



Swivel Plate
Total Brake
KPPTB



Hollow Kingpin
KPH



Hollow Kingpin
Total Brake
KPHTB



BEARING DESCRIPTION



Precision Ball (Q)


	Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Wheel Number
Thermoplastic Elastomer TPE (Precision Ball Bearing)	2 1/2	7/8	110	3 3/4	2 1/2	KJQ65G/
	3	7/8	110	4 1/8	2 3/4	KJQ75G/
	4	7/8	110	5 3/16	3 1/4	KJQ100G/

Rig Numbers	Swivel Plate Total Brake	Hollow Kingpin	Hollow Kingpin Total Brake	Color Way Code	ColorWay Description
Swivel Plate					
KPP	KPPTB	KPH	KPHTB	CPR RST ZBR TIM	Copper Thread Guard Russet Thread Guard Bronze Thread Guard Titanium Thread Guard



Caster Number: KJQ100G/KPHTBTIM
This 4" hollow Kingpin total brake rig with thermoplastic elastomer wheel and titanium color thread guard features a precision ball bearing.

Swivel lead dimension refers to KPP/KPH rigs.
Brake rig swivel lead is 3 1/2".



ZEN

Deluxe Medium Duty



FEATURES

- 5 year warranty on rig
- 3 year warranty on wheel
- ColorWays to match furniture, display or equipment
- Powder coated rig
- Chicago screw axle, domed both sides
- Excellent design and performance

RIG OPTIONS

Swivel Plate
MPPN



Swivel Plate
Total Brake
MPPNTB



Swivel Hollow
Kingpin
MPH



Swivel Hollow
Kingpin
Total Brake
MPHTB




A dependable caster that is suitable for everyday applications, the Zen M Series offers a sophisticated finish to a hard working caster, as it is available in four earth tones, which is perfect for a contemporary atmosphere.

TYPICAL APPLICATIONS


- Hospital beds
- Hospitality
- Food services
- Pharmaceuticals
- Dollies
- Store displays
- Stock carts
- Institutional

MOUNTING OPTIONS


North American Plate



Standard ISO Plate



Hollow Kingpin



To order delete **N** after rig code:
Example: MJQ100G/MPPNRST
changes to MJQ100G/MPPRST

BEARING DESCRIPTION



Precision Ball (Q)



Rig Numbers	Swivel Plate Total Brake	Hollow Kingpin	Hollow Kingpin Total Brake	Color Way Code	ColorWay Description
Swivel Plate					
MPPN	MPPNTB	MPH	MPHTB	CPR RST ZBR TIM	Copper Thread Guard Russet Thread Guard Bronze Thread Guard Titanium Thread Guard

Thermoplastic Elastomer TPE (Precision Ball Bearing)




Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rate for normal operation)	Overall Height (Inches)	Swivel Lead (Inches)	Wheel Number
3	1 1/4	190	4 3/16	2 7/8	MJQ75G/
4	1 1/4	200	5 5/16	3 9/16	MJQ100G/
5	1 1/4	220	6 3/8	4	MJQ125G/

MJ Note: MJQ wheels were formerly QXQ wheels



Caster Number: MJQ100G/MTHTBTIM
This 4" hollow Kingpin total brake rig with thermoplastic elastomer wheel and titanium color thread guard features a precision ball bearing.



Swivel lead dimension refers to MPPN/MPH Rigs. Brake rig swivel lead is 4 5/8" for 3" diam. wheels and 5" for 4" & 5" diam. wheels.

ZEN CASTERS • CAPACITY TO 220